



**NOTE:**

1. Wafer Material: Nylon 66 UL94V-2  
Pin/Pos Material: brass bronze.
2. Plated: Tin-plated 50u"min.
3. Insulation resistance: 1000MΩ/min.
4. Withstand voltage: 1000V AC/minute.
5. Current retang: 3A AC/DC.
6. Voltage rating: 250V AC/DC

**Dimensional & Ordering Information:**

Part No.	Circuits	Dim A	Dim B
251202HA054	2	2.50	5.00
251203HA054	3	5.00	7.50
251204HA054	4	7.50	10.00
251205HA054	5	10.00	12.50
251206HA054	6	12.50	15.00
251207HA054	7	15.00	17.50
251208HA054	8	17.50	20.00
251209HA054	9	20.00	22.50
251210HA054	10	22.50	25.00
251211HA054	11	25.00	27.50
251212HA054	12	27.50	30.00
251213HA054	13	30.00	32.50
251214HA054	14	32.50	35.00
251215HA054	15	35.00	37.50

REV.	REVISIONI			DIS	DATE	UNLESS OTHERWISE SPECIFIED TOLERANCES 3 PLACE ±0.5 ±0.10 2 PLACE ±1.5 ±0.25 1 PLACE ±2.0 ±0.50 ANGLE DIM
SCALE	REV.	PAGE:	UNIT	mm	DWG NO:	
4/1	A	1	THIRD ANGLE PROJECTION	⊕	C2512WV	

**EXCON**  
EXCON TECHNOLOGY COMPANY

PART.NO  
2512xxWV054

PART NO. 2512xxWV054  
DWG NO. C2512WV