




PART NO. 2541xxHA054  
 DWG NO. C2541HA



Dimensional and Ordering Information

Part No.	POS	A	B
254102HA054	2	2.54	5.7
254103HA054	3	5.08	8.2
254104HA054	4	7.62	10.8
254105HA054	5	10.16	13.3
254106HA054	6	12.70	15.9
254107HA054	7	15.24	18.4
254108HA054	8	17.78	20.9
254109HA054	9	20.32	23.5
254110HA054	10	22.86	26.0
254111HA054	11	25.40	28.6
254112HA054	12	27.94	31.1
254113HA054	13	30.48	33.6
254114HA054	14	33.02	36.2
254115HA054	15	35.56	38.7
254116HA054	16	38.10	41.3
254117HA054	17	40.64	43.8
254118HA054	18	43.18	46.3
254119HA054	19	45.72	48.9
254120HA054	20	48.26	51.4

NOTE:

- Housing Material:Nylon 66 UL94V-2
- Insulation resistance: 1000M ohm/min.
- Withstand voltage: 1000V AC/minute.
- Current retang: 3A AC/DC.
- Voltage rating: 250V AC/DC

				UNLESS OTHERWISE SPECIFIED TOLERANCES		 <b>EXCON TECHNOLOGY COMPANY</b>
				3 PLACE ±0.5 ±0.10		
				2 PLACE ±1.5 ±0.35		
				1 PLACE ±2.0 ±0.50		
				ANGLE DIM		
REV.	REVISIONI			DIS	DATE	
SCALE	REV.	PAGE:	UNIT	mm		DWG NO:
4/1	A	1	THIRD ANGLE PROJECTION			C2541HA
					DWG NO:	PART.NO
					C2541HA	2541xxHA054