



PART NO. 2546xxHA001
 DWG NO. C2546HA

Dimensional & Ordering Information:

Part No.	Circuits	Dim A	Dim B
254602HA001	2	2.54	5.70
254603HA001	3	5.08	8.24
254604HA001	4	7.62	10.78
254605HA001	5	10.16	13.32
254606HA001	6	12.70	15.86
254607HA001	7	15.24	18.40
254608HA001	8	17.78	20.94
254609HA001	9	20.32	23.48
254610HA001	10	22.86	26.02
254611HA001	11	25.40	28.56
254612HA001	12	27.94	31.10
254613HA001	13	30.48	33.64
254614HA001	14	33.02	36.18
254615HA001	15	35.56	38.72
254616HA001	16	38.10	41.26
254617HA001	17	40.64	43.80
254618HA001	18	43.18	46.34
254619HA001	19	45.72	48.88
254620HA001	20	48.26	51.42

NOTE:

1. Housing Material: Nylon 66 UL94V-0
2. Insulation resistance: 1000MΩ min.
3. Withstand voltage: 1000V AC/minute.
4. Current rating: 3A AC/DC.
5. Voltage rating: 250V AC/DC

				UNLESS OTHERWISE SPECIFIED TOLERANCES		EXCON EXCON TECHNOLOGY COMPANY
				3 PLACE ±0.5 ±0.10		
				2 PLACE ±1.5 ±0.20		
				1 PLACE ±2.0 ±0.30		PART NO 2546xxHA001
				ANGLE DIM		
REV.	REVISION			DIS	DATE	DWG NO: C2456HA
SCALE	REV.	PAGE:	UNIT			
5/1	A	1/1	THIRD ANGLE PROJECTION			