



Dimensional & Ordering Information:

Part No.	Circuits	Dim A
780402HAxxx	2	2.54
780403HAxxx	3	5.08
780404HAxxx	4	7.62
780405HAxxx	5	10.16
780406HAxxx	6	12.70
780407HAxxx	7	15.24
780408HAxxx	8	17.78
780409HAxxx	9	20.32
780410HAxxx	10	22.86
780411HAxxx	11	25.40
780412HAxxx	12	27.94
780413HAxxx	13	30.48
780414HAxxx	14	33.02
780415HAxxx	15	35.56
780416HAxxx	16	38.10
780417HAxxx	17	40.64
780418HAxxx	18	43.18
780419HAxxx	19	45.72
780420HAxxx	20	48.26
780421HAxxx	21	50.80
780422HAxxx	22	53.34
780423HAxxx	23	55.88
780424HAxxx	24	58.42
780425HAxxx	25	60.96
780426HAxxx	26	63.50
780427HAxxx	27	66.04
780428HAxxx	28	68.58



- NOTE:
- Housing Material: Nylon 66 UL94V2
  - Color:  $\Delta$  See table
  - Withstand voltage: 1500V AC/minute.
  - Plated: Tin 50u" min
  - Current rating: 3A AC/DC.
  - Voltage rating: 250V AC/DC

Color	AWG	Part NO
$\Delta$ Green	28	7804xxHA058
$\Delta$ Blue	26	7804xxHA059
$\Delta$ White	24	7804xxHA001
$\Delta$ Red	22	7804xxHA055

REV.	REVISION	DIS	DATE
3/1	A	1	

UNLESS OTHERWISE SPECIFIED TOLERANCES  
 3 PLACE  $\pm 0.5 \pm 0.10$   
 2 PLACE  $\pm 1.5 \pm 0.25$   
 1 PLACE  $\pm 2.0 \pm 0.50$   
 ANGLE DIM

SCALE: UNIT mm  
 DWG NO: C7804HA  
 THIRD ANGLE PROJECTION

PART.NO: 7804xxHAxxx