



Dimensional & Ordering Information:

Part No.	Circuits	Dim A
780402HB xxx	2	2.54
780403HB xxx	3	5.08
780404HB xxx	4	7.62
780405HB xxx	5	10.16
780406HB xxx	6	12.70
780407HB xxx	7	15.24
780408HB xxx	8	17.78
780409HB xxx	9	20.32
780410HB xxx	10	22.86
780411HB xxx	11	25.40
780412HB xxx	12	27.94
780413HB xxx	13	30.48
780414HB xxx	14	33.02
780415HB xxx	15	35.56
780416HB xxx	16	38.10
780417HB xxx	17	40.64
780418HB xxx	18	43.18
780419HB xxx	19	45.72
780420HB xxx	20	48.26
780421HB xxx	21	50.80
780422HB xxx	22	53.34
780423HB xxx	23	55.88
780424HB xxx	24	58.42
780425HB xxx	25	60.96
780426HB xxx	26	63.50
780427HB xxx	27	66.04
780428HB xxx	28	68.58

NOTE:

- Housing Material: Nylon 66 UL94V2
- Color: \triangle See table
- Withstand voltage: 1500V AC/minute.
- Plated: Tin 50u" min
- Current rating: 3A AC/DC.
- Voltage rating: 250V AC/DC

Color	AWG	Part NO
\triangle Green	28	7804xxHB058
\triangle Blue	26	7804xxHB059
\triangle White	24	7804xxHB001
\triangle Red	22	7804xxHB055

REV.	REVISION	DIS	DATE
3/1	A	1	

UNLESS OTHERWISE SPECIFIED TOLERANCES
 3 PLACE ±0.5 ±0.10
 2 PLACE ±1.5 ±0.25
 1 PLACE ±2.0 ±0.50
 ANGLE DIM



SCALE	REV.	PAGE	UNIT	mm	DWG NO:	PART.NO
3/1	A	1	THIRD ANGLE PROJECTION		C7804HB	7804xxHBxxx